



Cast. ceiling slab
 Metal flashing
 1/2" layer of plaster on cast
 metal flashing
 Plastic flashing
 Insulation cast with cast
 1/2" wood blocking fast to beam
 1/2" x 2" studs at 4'-0" o.c.

1/2" wood blocking fast to beam
 Cast and blocking as required by
 section 1014 - cast to beam with
 built-up strapping bolts from front to
 back of blocking
 Steel beam frame for window
 2 layers of 1/2" gypsum lath with
 1/2" plaster finish over, covered
 with metal & suspension system

Floor slabs - base of cast
 top of metal frame
 1/2" (or) wood cast
 Metal flashing of
 cast metal frame
 1/2" x 2" studs at 4'-0" o.c.
 1/2" wood blocking fast to beam
 1/2" x 2" studs at 4'-0" o.c.

1/2" wood blocking fast to beam
 1/2" x 2" studs at 4'-0" o.c.
 1/2" wood blocking fast to beam
 1/2" x 2" studs at 4'-0" o.c.

1/2" wood blocking fast to beam
 1/2" x 2" studs at 4'-0" o.c.
 1/2" wood blocking fast to beam
 1/2" x 2" studs at 4'-0" o.c.

SECTION THROUGH EAST-WEST COURT & WALL "A-B" on "D-M"

SECTION THROUGH EAST-WEST COURT & STORE FRONT

CONCORD HALL
 BIRMINGHAM, ALABAMA
 ARCHITECTS
 1234 5th Avenue
 Birmingham, Alabama